

ALMI Overview of Cables and Wires

	ALMI Cable Categories	++ high suitability		+ good suitability						- suitable				
		Factor high & low Temperature		Factor Flexibility						Factor Durability				
		Temperature range in continuous operation		Dynamic applications						Chemicals, solvents	Oils, grease	UV, ozone, weather	Wear resistant	
		from	to	Flexibility	Cable trolley	Drag chain	Spreader	Torsion	Reelable cable	Roboter				
1	ALMI Multoflex	-5°C	+70°C	+	-	-	-	-	-	-	-	-	+	-
2	ALMI Multoflex low temp. resistant	-20°C	+70°C	+	-	-	-	-	-	-	-	-	+	-
3	ALMI Multoflex heat resistant	-5°C	+105°C	+	-	-	-	-	-	-	-	-	+	-
4	ALMI Multoflex special oil resistant	-5°C	+70°C	+	-	-	-	-	-	-	++	-	-	-
5	ALMI ALL-FLEX	-40°C	+80°C	++	++	+	++	+	++	+	+	+	+	+
6	ALMI Suprex	-40°C	+80°C	++	++	+	++	+	++	-	+	+	++	++
7	ALMI Welding Cable	-40°C	+80°C	++							+	+	++	+
8	ALMI PREXTHAN	-40°C	+80°C	++	++	++	++	++	++	++	+	+	+	++
9	ALMI PREXTHAN 110	-30°C	+110°C	++	++	++	++	++	++	++	+	+	+	++
10	ALMI PREXTHAN 120	-40°C	+120°C	++	++	++	++	++	++	++	+	+	+	++
11	ALMI IDURTHERM 145	-55°C	+145°C	-							+	+	+	+
12	ALMI HIFP 155	-65°C	+155°C	-	-	-	-	-	+	-	++	++	++	++
13	ALMI SUPREX-THERM	-20°C	+180°C	+	+	+	+	-	+	-	++	++	++	++
14	ALMI HAFL	-50°C	+180°C	+	+	+	+	+	+	-	-	-	-	+
15	ALMI HAFL-S Profibus-Therm	-40°C	+180°C	+	+	+	+	+	+	-	-	-	-	+
16	ALMI HAFL-S CAT6-Therm	-40°C	+180°C	+	+	+	+	+	+	-	-	-	-	+
17	ALMI B-SI-K	-50°C	+180°C	+	+	+	+	+	+	-	-	-	-	+
18	ALMI SSID	-50°C	+180°C	++	+		+	+	-	-	-	-	-	+
19	ALMI SSHT Smelting Plant Cable	-40°C	+180°C	+	-	-	-	-	-	-	-	-	-	-
20	ALMI SSHT-SI Smelting Plant Cable	-40°C	+180°C	+	+	-	-	-	-	-	-	-	-	+
21	ALMI HIFP Profibus-Therm	-50°C	+180°C	-							++	++	++	++
22	ALMI HIFP CAT6-Therm	-40°C	+200°C	-	-	-	-	-	-	-	++	++	++	++
23	ALMI HIFP Profibus-Therm M200	-100°C	+180°C	+	-	-	-	-	-	-	++	++	++	++
24	ALMI HIFP 205	-100°C	+205°C	+	-	-	-	-	-	-	++	++	++	++
25	ALMI HIFP 260	-190°C	+260°C	+	-	-	-	-	-	-	++	++	++	++
26	ALMI HIGHFLAME	-65°C	+260°C	-	-	-	-	-	-	-	-	-	-	-
27	ALMI HIGHFLAME 350	-65°C	+350°C											
28	ALMI HIGHFLAME 450	-65°C	+450°C											
29	ALMI HIGHFLAME 600	-65°C	+600°C											
30	ALMI HIGHFLAME 800	-65°C	+800°C											
31	ALMI HIGHFLAME 1000	-65°C	+1000°C											
32	ALMI HIGHFLAME 1200	-65°C	+1200°C											
33	ALMI AGL - Compensating Cables	-190°C	+1200°C	+							++	++	++	++
34	ALMI THL - Extension Cables	-190°C	+1200°C	+							++	++	++	++

Possible use to be clarified for each individual application.

The product matrix reflects the general product range of Alfred Michels GmbH & Co. KG. Additional speciality production possible.

Numerous types available from stock according to design (no. of cores x cross section), special manufacture from 100 m lengths.